

Horizon[®] Ci

Multi-media Imager



Horizon[®] Ci




Multi-media Imager

Overview

The Horizon Ci combines diagnostic film, color paper and grayscale paper printing to provide the world's most versatile medical imager. Horizon's multiple media options help to immediately cut your costs, build referring physician loyalty and attract new business. High speed image processing, networking and spooling are standard.

Specifications

Print Technology:	Dye-diffusion and direct thermal (dry, daylight safe operation)
Spatial Resolution:	320 DPI (12.6 pixels/mm)
Throughput:	Up to 100 films per hour
Time To Operate:	5 minutes (ready to print from "off")
Grayscale Contrast Resolution:	12 bits (4096)
Color Resolution:	16.7 million colors 256 levels each of cyan, magenta, and yellow
Media Inputs:	Three supply cassettes, 50 - 100 sheets each, one color ribbon
Media Outputs:	Three receive trays, 50-sheet capacity each
Media Sizes:	8" x 10", 14" x 17" (blue and clear) DirectVista [®] Film A, A4, 14" x 17" DirectVista Grayscale Paper A, A4 ChromaVista [®] Color Paper and Color Film*
Dmax:	≥3.10 with DirectVista Film
Archival:	≥20 years with DirectVista Film, under ANSI extended-term storage conditions
Supply Cassettes:	All media is pre-packaged in factory sealed, disposable cassettes
Interfaces:	Standard: 10/100 Base-T Ethernet (RJ-45), Serial Diagnostic Port, Serial Console Optional: DICOM (up to 24 simultaneous connections), Windows network printing
Network Protocols:	Standard: FTP, LPR Optional: DICOM, PostScript [™] compatibility
Image Formats:	Standard: TIFF, GIF, PCX, BMP, PGM, PNG, PPM, XWD, JPEG, SGI (RGB), Sun Raster, Targa
Optional:	DICOM, PostScript [™] compatibility
Image Quality:	Automatic calibration using built-in densitometer
Image Control:	Gamma, Contrast, Saturation, Medical Color Matching (MCM [™]), Polarity, Rotation, Scaling, Antialiasing
Sheet Control:	Density Adjustment (Dmax), Look-Up Tables (LUT), Image Warnings, Captions, Sheet Coverage, Border Color, Border Fill, Crop Anchor
Sheet Formatting:	1:1 - 1:81; Variable Multi-Formatting (VMF [™]), Fixed Multi-Formatting (FMF [™]), 35mm SlideMaker [™]
Control Panel:	Large, backlit LCD display, Status lights include Online, Alert, Fault, Active Power and Menu navigation buttons
Processor:	Intel
Memory:	256MB RAM
Hard Disk:	20 GB (18GB available for spooling)
Removable Disk:	100MB ZIP [™] Disk for software upgrades
Smart Card:	32 KB for storing configuration data
Power:	Universal Input: 100-120/230V~ 50/60 Hz, 600W printing, 150W idle
Heat Emission:	Maximum 600W, 2,050 BTUs/hr. printing, 150W, 512 BTUs/hr. idle
Weight:	66 lbs. (30 kg.)
Engine Dimensions:	14.5" (37 cm) H, 20.5" (52 cm) W, 24" (61 cm) L
Environment:	Operating Temperature: 15-30C Storage: -22.2 - 50.6C Operating Humidity: 10-70% R.H. (non-condensing)



A Class 1 laser product according to IEC 60825-1 and 21 CFR 1040.10 and 1040.11.

Call Codonics today at **800-444-1198** or visit **www.codonics.com** for more information.

* Horizon Color Film is a work-in-progress. All registered and unregistered trademarks are the property of their respective owners. Specifications subject to change without notice. Patents pending. Copyright © 2006 Codonics, Inc.



17991 Englewood Drive
Middleburg Heights, OH 44130 USA
(440) 243-1198
(440) 243-1334 Fax
Email info@codonics.com
www.codonics.com